

Cat6A/7 Connector, 28–26 AWG



90180

This shielded Cat6A/7 RJ45 (8P8C) modular connector is designed to terminate round solid or stranded, 28 – 26 AWG, Cat6A/7 network cable. The connector contains 3-Prong contacts that hold the wire in place giving a reliable connection. This connector meets and exceeds 10Gig performance standard.

Features

- Cable Jacket Outer Diameter Size Range: 0.224" – 0.335" (5.7mm – 8.5mm)
- Insulation Diameter (Conductor) Size Range: 0.037" – 0.041" (0.94mm – 1.05mm)
- Designed for both shielded and unshielded cabling
- Compatible with CAT7, CAT6A, CAT6E, and CAT6
- Meets ANSI/EIA/TIA/TAA specifications
- Round Solid and Stranded, 28–26 AWG
- Shielded Connector, External Ground
- 3-Prong, 50 micron Gold plated Contacts
- 3 Piece with Liner and Spacer Bar
- Meets 10Gig Performance Standard
- UL and RoHS/FCC compliant
- Color: Clear/Transparent

Compatible Crimp Tool

- Tele-Titan™ Xg 2.0 Crimp Tool (P/N 12516C)

Ordering Information

P/N	Description	Quantity
106240	RJ45 Cat6A/7, STP, Solid/Stranded, 28–26 AWG.	100/Bag
106241	RJ45 Cat6A/7, STP, Solid/Stranded, 28–26 AWG.	25/Bag
106242	RJ45 Cat6A/7 STP, Solid/Stranded, 28–26 AWG.	50/Bag
106243C	RJ45 Cat6A/7, STP, Solid/Stranded, 28–26 AWG.	10/Clamshell
106244	Spare Liners.	50/Bag
106245	Spare Spacer Bars.	50/Bag
90180	Cat6A/7 28–26 AWG Termination Kit	1/Box

California, USA

Phone: 805.384.2777 / 800.749.5783 • Fax: 800.749.5784

www.platinumtools.com

We Make Connections EZ!™